



Contents

Synopsis

Acknowledgements

xii

1 Introduction

1

1.1 General	1
1.2 Restructured electrical power system and its models	3
1.2.1 Generating Companies (GENCOs)	4
1.2.2 Transmission Companies (TRANSCOs)	4
1.2.3 Distribution Companies (DISCOs)	4
1.2.4 Customers	4
1.2.5 Market Operator	5
1.2.6 Independent System Operator (ISO)	5
1.2.7 Aggregators	6
1.2.8 Brokers	6
1.2.9 Retail Companies (RETAILCOs)	6
1.2.10 Energy market	8
1.2.11 Ancillary service market	8
1.2.12 Transmission market	9
1.2.12.1 PoolCo model	9
1.2.12.2 Bilateral Contract model	9
1.2.12.3 Hybrid model	11
1.3 Main FACTS controller	11
1.3.1 Thyristor Controlled Series Compensator (TCSC)	13

1.3.1.1	Operating modes of TCSC	14
1.4	State-of-the-Art	18
1.4.1	Optimal placement of FACTS for maximization of TTC and minimiza- tion of losses	19
1.4.2	Social welfare maximization	20
1.4.3	Impact of FACTS devices on pricing, wheeling charges and secure bi- lateral transactions	22
1.4.4	Congestion management	23
1.5	Motivation	24
1.6	Thesis Organization	27
2	Particle Swarm Optimization (PSO)	29
2.1	General	29
2.2	Step by step procedure for implementing PSO	32
2.3	Literature review:PSO applications in Electric power systems	33
2.3.1	Economic load dispatch	33
2.3.2	Reactive power management	35
2.3.3	Optimal power flow	36
2.3.4	Power System Controller Design	37
2.3.5	Neural Network Training	38
2.3.6	Price forecasting and Load forecasting	38
2.3.7	Other Power System Areas	39
2.4	Advantages of PSO	42
2.5	Disadvantages of PSO	42
2.6	Conclusions	43
3	Optimal placement of Thyristor Controlled Series Compensator (TCSC) for Total Transfer Capability (TTC) enhancement	44
3.1	Introduction	44
3.2	TTC definitions and related terms	46
3.2.1	Available Transfer Capability (ATC)	46
3.2.2	Total Transfer Capability (TTC)	47

3.2.2.1	Scheduling Horizon (Real-time):	47
3.2.2.2	Operating horizon (Pre-schedule/Day ahead)	48
3.2.2.3	Planning horizon	48
3.2.3	Transmission Reliability Margin (TRM)	49
3.2.4	Existing Transmission Commitments (ETC)	49
3.2.5	Capacity Benefit Margin (CBM)	49
3.2.6	Curtailability	50
3.2.7	Recallability	50
3.3	Calculation of total transfer capability and some technical challenges	50
3.3.1	Voltage limits	51
3.3.2	Stability limits	51
3.3.3	Parallel path flows	52
3.3.4	Maintaining voltage levels	52
3.3.5	Projected customer demand	52
3.3.6	Contingency analysis	53
3.3.6.1	General	53
3.3.6.2	Operating criteria and study standards	53
3.4	Static modeling of Thyristor Controlled Series Compensator (TCSC)	54
3.5	Proposed PSO based algorithm to optimally locate TCSC for maximizing TTC and minimizing losses	56
3.5.1	Optimal power flow model	57
3.5.2	Modeling of bilateral and multilateral transactions	60
3.5.3	Contingency analysis	60
3.5.4	Step by step algorithm to optimally locate TCSC for maximizing TTC and minimizing losses using PSO	61
3.6	Results and Discussions	62
3.6.1	IEEE 30-bus test system	62
3.6.2	UPSEB 75-bus test system	65
3.6.3	Effect of PSO parameters on the value of TTC	68
3.7	Conclusions	70

4 Optimal placement of Thyristor Controlled Series Compensator (TCSC) for Social Welfare enhancement	72
4.1 Introduction	72
4.2 OPF formulation and swarm initialization in PSO	80
4.2.1 Initialization of a population	81
4.2.2 Installation of a TCSC	82
4.2.3 Power flow	82
4.2.4 Optimal power flow problem formulation	83
4.3 Social welfare of various market participants	86
4.4 PSO based algorithm to optimally locate TCSC to maximize social welfare .	87
4.5 Results and Discussions	88
4.5.1 IEEE 6-bus test system	89
4.5.1.1 Effect of PSO parameters on convergence	92
4.5.2 IEEE 30-bus test system	94
4.5.3 UPSEB 75-bus test system	99
4.6 Conclusions	103
5 Impact of optimally placed TCSC on transmission pricing, wheeling charges and bilateral transactions	104
5.1 Introduction	104
5.2 OPF formulation and swarm initialization in PSO	107
5.2.1 Initialization of a population	107
5.2.2 Installation of a TCSC	107
5.2.3 Power flow	109
5.2.4 Optimal power flow problem formulation	109
5.3 Active and Reactive power spot prices for generators	112
5.4 Active and Reactive power spot prices for consumers	114
5.5 Basic concept of wheeling charges	115
5.5.1 Embedded cost based pricing:	116
5.5.2 Incremental cost based pricing:	116
5.5.3 Combination of above two methods:	116

5.5.4	Flat Fee method:	116
5.5.5	Postage Stamp method:	117
5.5.6	MW-Mile method:	117
5.5.7	Contract path method:	117
5.5.8	Rated system path method:	117
5.5.9	Location Based Marginal (LBM) costing:	117
5.6	Computation of wheeling rates	118
5.7	Basics of bilateral transaction	119
5.8	Results and Discussions	120
5.8.1	IEEE 6-bus test system	121
5.8.2	IEEE 30-bus test system	129
5.8.3	UPSEB 75-bus test system	133
5.9	Conclusions	138
6	Sensitivity and PSO based congestion management	140
6.1	Introduction	140
6.2	Formulation of sensitivity factors	141
6.2.1	Optimal power flow problem formulation	144
6.2.2	PSO based algorithm for congestion management	148
6.3	Results and Discussions	149
6.3.1	IEEE 30-bus test system	150
6.3.1.1	Statistical results and convergence characteristic of PSO . .	154
6.3.2	UPSEB 75-bus test system	155
6.4	Conclusions	160
7	Conclusions	162
7.1	General	162
7.2	Summary of Important Findings	163
7.3	Scope for future research	166
	Bibliography	168
A	Data for 6-bus test system	184

CONTENTS

xviii

B Data for IEEE 30-bus test system

188

C Data for UPSEB 75-bus system

194