
List of Figures

2.1	MIMO wireless communication model	8
2.2	SIMO System-Channel Capacity	11
2.3	MISO System-Channel Capacity	11
2.4	MIMO System-Channel Capacity	12
2.5	Capacity vs Number of receive antenna for SIMO system	14
2.6	Capacity vs Number of transmit antenna for MISO system	14
2.7	Capacity vs Number of receive antenna for MIMO system	15
2.8	10 percent Outage capacity of MIMO System	17
2.9	90 percent Outage capacity of MIMO System	17
2.10	BER for different diversity order	19
2.11	Diversity Multiplexing trade-off of MIMO System	22
2.12	Diversity Multiplexing tradeoff of MISO and MIMO system	22
2.13	MIMO Transmission techniques and their performance gains	23
2.14	GUI for MIMO Wireless Simulator	25
2.15	Comparison of ZF, ML and MMSE reciver for V-BLAST Technique	25
2.16	Comparison of BER for Diversity Techniques: Alamouti, STBC and STTC	26
3.1	System Design Methodology	29
3.2	Basic Hardware Architecture of MIMO	30
3.3	Model Based Design Methodology	33
3.4	Programming and Verification steps for FPGA	34
3.5	Programming and Verification steps for DSP	36
3.6	Front View of FTE Wireless Robot	37
3.7	Back View of FTE Wireless Robot	37
3.8	Snapshot of SiLabs IDE	38
3.9	FTE Robot with Wireless module connection	40
3.10	Connections between FTE Robot and Wireless Module	40
3.11	Snapshot of Pololu Wixel Configuration Utility	41
3.12	Implementation of Wireless Control of FTE Embedded Robot	41
4.1	Performance of LTE MIMO with different antenna schemes	44
4.2	E-UTRAN Architecture	45
4.3	E-UTRA radio interface protocol architecture	46
4.4	Frame Structure Type 1 (FDD)	49
4.5	LTE Resource Grid	50
4.6	LTE Physical Channel Processing with Uplink Feedback	51
4.7	Downlink Physical Layer Processing	52
4.8	2x2 Transmit Diversity Transmission Mode	54
4.9	Open Loop Spatial Multiplexing	54
4.10	Close Loop Spatial Multiplexing	54
4.11	Structure of Link Level Simulator	55
4.12	Throughput v/s SNR for MIMO antenna configuration in LTE-A	59
4.13	Throughput and BLER for Transmit Diversity	60
4.14	Throughput and BLER for Spatial Multiplexing	61

4.15	Throughput and BLER for Transmit Diversity and Spatial Multiplexing	62
4.16	Comparison of MIMO Transmission modes in LTE-A	64
4.17	Throughput for Transmission modes with Flat rayleigh	65
4.18	Comparison of Throughput for SNR=30dB	65
5.1	Various Problem Solving Techniques	68
5.2	Fuzzy Logic System	69
5.3	Fuzzy Inference System Editors and Viewers	71
5.4	FLC in Simulink	72
5.5	McCulloch-Pitts model neuron	73
5.6	Artificial Neuron	74
5.7	(a) Feed-forward (FNN) and (b) Recurrent Neural Network (RNN) Architectures	75
5.8	Neural Network Toolbox	77
5.9	Neural Network Simulink model	78
5.10	Neural Network Toolbox Simulink Blocks	79
5.11	Genetic Algorithm Basic Structure	81
5.12	Optimization App in Global Optimization Toolbox	82
6.1	Reference Signals for LTE-A antenna ports	86
6.2	ANN based Channel estimation	88
6.3	Feedforward Neural Network	89
6.4	Radial Basis Network	89
6.5	Layer Recurrent Neural Network	90
6.6	Generalized Regression Neural Network	90
6.7	Throughput v/s SNR for TxD 2x2 for various ANN Channel estimation	92
6.8	Throughput v/s SNR for CLSM 2x2 for various ANN Channel estimation	92
6.9	Comparison of Elapsed Time for different MIMO Channel Estimation Techniques	93
6.10	ANN-GA based Channel Estimation	94
6.11	Throughput v/s SNR for ANN-BPA and ANN-GA MIMO Channel Estimation	96
7.1	Channel capacity with varying SNR	100
7.2	Channel capacity with varying Condition Number	100
7.3	CDF of SCN for Uncorrelated Rayleigh Channel	101
7.4	PDF of SCN for Uncorrelated Rayleigh Channel	101
7.5	CDF of SCN for semicorrelated Rayleigh Channel	102
7.6	PDF of SCN for semicorrelated Rayleigh Channel	102
7.7	Switching point between 2x2 TxD and OLSM for different transmit correlation	104
7.8	Block Diagram for FL Decision based MIMO mode Switching	105
7.9	Membership function for Channel Condition Number	107
7.10	Membership function for Receive-SNR	107
7.11	User Interface for FL Decision model for MIMO mode switching	110
7.12	Comparative Analysis of FL Decision Model for Initial mode of TxD 4x2	111
7.13	Comparative Analysis of FL Decision Model for Initial mode of OLSM 2x2	112
7.14	Comparative Analysis of FL Decision Model for Initial mode of OLSM 4x2	113
7.15	Comparative Analysis of FL Decision Model for Initial mode of TxD 4x2.	114
8.1	Design Flow for Real-time Implementation on Target Hardware	116
8.2	XUP Atlys Spartan-6 Development Kit	117
8.3	Functional Block Diagram of Atlys board	118

8.4	TMS320C6713 DSP Starter Kit	119
8.5	Functional Block Diagram of DSK 6713	119
8.6	Simulink Models for FL Decision model for HDL Co-simulation and FIL Simulation	120
8.7	ModelSim Simulator Results	121
8.8	Simulink Model for FL Decision model for SIL and PIL Simulation	122
8.9	Code Composer Studio IDE Window	123
8.10	Throughput Analysis of Case 1 Scenario	124
8.11	Throughput Analysis of Case 2 Scenario	124
8.12	Throughput Analysis of Case 3 Scenario	125
8.13	Throughput Analysis of Case 4 Scenario	125
8.14	Throughput Analysis of Case 5 Scenario	126
8.15	Throughput Analysis of Case 6 Scenario	126
8.16	ANN based MIMO Channel Estimation Simulink Model	127
8.17	Throughput Analysis of GRNN Case 1	129
8.18	Throughput Analysis of GRNN Case 2	129
8.19	Throughput Analysis of GRNN Case 3	130
8.20	Throughput Analysis of GRNN Case 4	130
8.21	Throughput Analysis of GRNN Case 5	131
8.22	Throughput Analysis of GRNN Case 6	131
9.1	Throughput for different antenna configuration in LTE-A Downlink Physical Layer	134
9.2	Comparison of Throughput for GRNN channel estimation and implementation	135
9.3	Comparison of throughput for FL Decision model and hardware implemntation	136
9.4	GUI for analysis of MIMO Communication System	137
A. 1	GUI for Design and Implementation of Embedded Architecture Using Soft-Computing Techniques for Parametric Optimization of MIMO Wireless System	162
A. 2	GUI for MIMO Wireless Simulator	163
A. 3	Features of MIMO Wireless Simulator	164
A. 4	MIMO WS GUIs for performance analysis	164
A. 5	STTC performance analysis GUI	165
A. 6	GUI for FL decision model for MIMO mode switching	165
A. 7	Programming XUP Atlys board through MATLAB FIL model	166
A. 8	Programming C6713DSP through MATLAB PIL model	166
A. 9	GUI for Throughput Analysis for ANN based MIMO channel estimation	167
B. 1	FTE Robot with Wireless module: 1)FTE Robot, 2)Connecting wires between Robot and Wireless Module and 3)Wireless Module.	171
B. 2	Wireless Control of FTE Robot setup: 1)Remote Computer, 2) FTE Robot with wireless module, 3) Transmitter Wireless Module, 4) JTAG Adapter Connector	171
B. 3	DSP Starter Kit: 1)TMS320C6713 DSP, 2)JTAG Emulation, 3)Power Jack, 4)USB Port, 5)Memory Expansion and 6)AIC23 Codec with peripherals	172
B. 4	DSP Setup: 1)CPU Core2Duo with Software tools installed, 2)TMS320C6713 DSK, 3)Power Cable and 4)USB Cable	172
B. 5	XUP Atlys Board: 1)Spartan-6 LX 45, 2)Adept USB Port, 3)Power Jack, 4)Ethernet connector, 5)VHDC connector and 6)LEDs, Slide Switches and Push buttons	173
B. 6	FPGA Setup: 1)CPU Core2Duo with Software tools installed, 2)USB cable, 3)Power cable, 4)Atlys board, 5)Gigabit Ethernet crossover cable	173