

INTEGRATION OF DISTRIBUTED GENERATORS AND STORAGE DEVICE IN MICROGRID

*A Thesis Submitted
for the Award of the
Degree of*

DOCTOR OF PHILOSOPHY

in

Electrical Engineering

By

Parul Anand Upadhyay



DEPARTMENT OF ELECTRICAL ENGINEERING
FACULTY OF TECHNOLOGY & ENGINEERING
THE MAHARAJA SAYAJIRAO UNIVERSITY OF BARODA

JUNE 2022

Declaration

I Parul Anand Upadhyay hereby declare that the work reported in this thesis entitled **INTEGRATION OF DISTRIBUTED GENERATORS AND STORAGE DEVICE IN MICROGRID** for the award of the degree of DOCTOR OF PHILOSOPHY in the Electrical Engineering Department, Faculty of Technology & Engineering, The Maharaja Sayajirao University of Baroda, Vadodara. I further declare that the thesis is not substantially the same as one, which has already been submitted in the part or in full for the award of any degree academic qualification of this university or any other institution or examining body in the India or abroad.

(Parul A Upadhyay)

June 2022.

Contents

1	Introduction	1
1.1	General	1
1.2	State-of-the-Art	3
1.2.1	Optimisation Approach for the Placement of DG	3
1.2.2	Model of Renewable DG	14
1.3	Motivation	18
1.4	Thesis Organization	20
2	Wind power Generation unit Model	22
2.1	Introduction	22
2.2	Wind System	24
2.2.1	Average Power in Wind	24
2.2.2	Wind Speed Distribution Function	25
2.2.3	Wind Generation Unit	27
2.3	Weibull Probability Distribution Function	29
2.3.1	Estimation of value of k and c	29
2.4	Wind Power Analysis	31
2.4.1	Data Source	31
2.4.2	Wind Speed Statistics and Power Generation Model	32
2.5	Result and Discussion	33
2.5.1	Wind Power Generation Model using Wind States	37
2.6	Conclusion	39
3	Solar power Generation unit Model	40
3.1	Introduction	40

3.2	Solar Photovoltaic System	41
3.2.1	Photovoltaic Generation Modelling	42
3.3	Beta probability distribution	44
3.4	Solar Irradiation Modelling and Analysis	45
3.4.1	Data sources	45
3.4.2	Solar Power Probability by Beta pdf	46
3.5	Result Analysis	47
3.6	Conclusion	54
4	Optimal Summation of Natural Power resources in Microgrid	57
4.1	Introduction	57
4.2	Microgrid Technology	60
4.2.1	Microturbines	61
4.2.2	Natural Power sources	61
4.2.3	Fuel cells	61
4.2.4	Storage Devices	62
4.2.5	Microgrid Benefits and Challenges	62
4.3	Microgrid Model	63
4.4	Backward Forward Sweep Power Flow	65
4.4.1	Backward Sweep Process	66
4.4.2	Forward Sweep Process	66
4.4.3	Nodal Analysis using Convergence Criteria	67
4.5	Application of Backward Forward Load Flow to Radial Distribution System	67
4.5.1	NPDG data	67
4.5.2	Network and load data	68
4.6	Application of Backward Forward load flow on IEEE 13 node Distribution syatem for placement of NPDG	69
4.6.1	Load Flow Result and Discussion	70
4.7	Optimisation Problem formation strategy and solution	72
4.7.1	Objective Function	72
4.7.2	Optimisation Problem Solution and Discussion	75
4.8	Conclusion	76

5	Optimum integration of Wind and Solar unit using Levy flight PSO.	84
5.1	Introduction	84
5.2	An Enhanced particle Swarm optimizer Algorithm with Levy flight	88
5.2.1	Levy Flight Distribution	89
5.3	IEEE-13 node Distribution System as Microgrid	91
5.4	Problem Formation	92
5.4.1	Nomenclature	92
5.4.2	Objective Function	93
5.4.3	System constraints	95
5.5	Steps to Solve Optimization Problem Using LFPSO for 12-node Grid connected Microgrid	97
5.6	Simulation Result and Discussion	99
5.7	Conclusion	106

Executive Summary

INTEGRATION OF DISTRIBUTED GENERATORS AND STORAGE DEVICE IN MICROGRID

Brief Research Methodology

Now a days, the trend in electric power generation is to employ power generation sources ranging from kW to MW near load locations rather than traditional centralised sources with larger MW and positioned far from the loads where natural resources are available. The installation and operation of a portfolio of small, compact, and clean electric power generating units are key components of this electric power generation technology. The small, compact, and clean electric power generating units near to the load are known as Distributed Generators(DGs). The penetration of DG units must required appropriate planning in distribution network to face challenges such as high cost, high network losses, reliability, voltage rise, voltage stability, power-fluctuation. Use of renewable DG depends of availability of natural resources and geographical condition of location. The purpose of integrating Distributed Generators (DGs) and storage devices is to provide a solution to the issues of renewable and nonrenewable DG penetration by determining the optimal location and size for each. Integration of DGS and storage devices improves distribution system management as a grid connected or autonomous microgrid by considering their types and availability. Prevalent state-of-art reveals few missing links or research gaps, and the same could be presented as:

- The articles which have been published presented research work in the context of

accommodating renewable and nonrenewable generators in the distribution system. The primary goal of these studies was to reduce losses and improve voltage stability. Reduced losses and improved voltage profiles can alter the power drawn from the main grid by the distribution network. In the literature, this aspect has gained no attention.

- The problem of establishing the placement and size of DG has been solved by considering DG such as synchronous generators, biomass-based microturbines, solar, and wind independently. The impact of combined DG installation has not been extensively researched.
- Many papers assumed weibull pdf and beta pdf parameters for wind speed and solar irradiation modelling. After obtaining this model, an examination of the influence of the NPDG has been performed. In fact, the weibull pdf and beta pdf parameters change over time.
- Only a few hybrid optimization algorithms have been addressed for the installation, planning, and operation of microgrids with renewable and nonrenewable DG. It motivates the development of a new hybrid strategy that provides robust operation and planning for renewable DG in the presence of uncertainty.
- The majority of work has been published in order to reduce the installation or operational costs of microgrids using renewable and nonrenewable DGs. The cost of under and overestimation of natural resources was not considered when developing the cost function. This could be critical in the case of a microgrid powered by renewable energy.

The work in this thesis is organized in a chaptered manner to alleviate and address the presented gaps, as

- **chapter-1**, discusses the dominance of renewable distributed generators (DG) in the power system, as well as their classification, the concept and benefits of microgrid, and the problems of microgrid design and management. This chapter also represents state-of-art of application of Particle Swarm Optimisation(PSO), enhanced PSO for optimal placement of various type of DG and significance of microgrid management system, modelling of wind and solar distributed sources. It discusses about the

prime factors that have need to the emergence while planning the operation and control of microgrid with renewable and non renewable DG and motivation behind this work.

- **Chapter-2**, presents analysis of the weibull probability distribution function to develop wind power generation model. The estimation of the output power generation of wind unit has been carried out on the basis of shape and scale parameter of pdf. The historical data has been canalised to justify the selection of shape parameter to compute hourly average power generation for the given size of wind unit. The integration of wind speed probability for discrete state has been done to develop probable wind power generation model.
- **Chapter-3**, explores the methodology to determine potential of solar power unit per day on any selected site. The beta probability distribution function has been described to calculate hourly average energy generated of given solar unit. The integration of solar irradiation probability for discrete state has been done to develop probable solar power generation model.
- **Chapter-4**, finds the optimal sitting of single and hybrid DG unit without storage device for all combination of placement using forward -backward load flow for minimum grid losses. It also gives detailed description of forward -backward load flow. The finding has been bring out on IEEE-13 node distribution system. The objective function has been designed to achieve technical benefits of summation of natural power distributed generators. The PSO has been executed to solve optimisation problem. The result of both method has been compared regarding grid and substation dependency factor.
- In **Chapter-5** The modification of optimisation problem has been presented for the integration of Distributed generators and storage devices in microgrid planning and operation. A levy flight PSO algorithm has been used to obtain optimal value of variables and fulfill the objectives.
- **Chapter-6**, summarizes the contribution of the thesis and also provides a few suggestions for the future expansion of this work.

Key Findings

The findings of the work that has been carried out, has been summarized as follows: In chapter-2 the energy generation/day and power production/specific time period has been computed by four ways.

1. Assume fixed value of shape parameter- k by studying historical data of wind speed.
2. Choose Rayleigh pdf means shape parameter- $k = 2$.
3. find value of shape parameter- k for specific time slot/day by statistical analysis of historical data of wind speed
4. consider power probability as per wind speed state and shape parameter- k has been calculated from wind statistics for a one quarter.

The identical result has been obtained from the method no:3 and 4. However, In the case of state-wise probability (method-4), the length of computational steps and time are less. As a research point of view, wind models with Shape parameter $K=2$ (Rayleigh) may not always be applicable to develop unique methods. As a result, a thorough analysis about wind speed and probable wind power has been carried out. This analysis has been used to plan the optimal installation, operation and control of the power grid, and scheduling of the power plant. This model is also useful for reducing estimation error in wind power forecasting and maximising natural resource utilisation in the power grid. The model which is discussed in chapter -2 is applied to plan summation of wind power resource with conventional DG in the microgrid.

The solar power generating model was established following a detailed analysis of the sun radiation at the chosen location-Town Cambay, along the seaside of Gujarat state. The solar radiation potential has been evaluated using beta pdf which is obtained on hourly basis. the solar energy generation/day and solar power production/specific time period has been computed by two way.

1. On the basis of hourly mean solar radiation.
2. hourly solar radiation is divided in four states.

When state-by-state probability is taken into account, the estimation of average solar energy generated per hour in first and second quarters is 25% greater. The probable energy produced per hour during the quarter-3 is less than that produced by the preliminary technique. During the fourth quarter period, the hourly average energy generated by both the way is the same. The result of estimation has been verified with the readily available solar power production tools.

The studies conducted in Chapter-5 reveals about Particle Swarm Optimization (PSO) for finding optimal summation of solar, wind and microturbine in microgrid. A microgrid power flow analysis with backward forward load flow has been carried out to determine system losses and nodal voltage and phase angle. The development of an optimal problem strategy for determining the placement and size of NPDG and micro turbines in grid-connected microgrid has been presented in this chapter. The hourly average probable power generation of wind and solar units has been taken into account as the maximum power generation limit of that unit for the reliable operation of a distributed power system. In order to minimise losses and reliance on the main grid, the highest loaded node is the best optimum location for any DG having a maximum power generation limit. It is proved that the PSO method is far better to get value of fitness function regarding optimal integration of renewable and non renewable DGs in microgrid.

A novel approach, Levy flight Particle Swarm Optimization has been discussed in chapter-5 to solve optimisation problem on planning and operation of microgrid along with renewable and non renewable DGs. The fitness function has been developed by including in DG Levelized energy costs, grid losses, system restrictions, and microgrid reliance on the main substation. The average of G_{best} value has been obtained for IEEE 13 bus distribution test system. Hence, Levy flight Particle Swarm Optimization provides the optimum value of objective function.

Conclusion

optimal planning and operation of microgrid on the basis of potential analysis of the renewable power resources has been carried out in this study. Estimation of wind and solar power generation have been investigated by collecting wind data of

selected site. The wind speed has been analysed using Weibull probability function, in which time slot wise shape parameter as well as fixed value of shape parameter have been utilised. The solar irradiation has been analysed using beta pdf in which parameters have been found hourly and state wise. From the wind speed statistics and the Weibull pdf, it is proved that in the periods- April to June and July to September, possibility of power production using wind turbine unit is good. Results of solar irradiation analysis shows good potential of the solar energy in most of the period. During the period July to sept low potential of solar energy. It is because of cloudy day in that period. The wind and solar power generation model have been developed based on natural source (wind speed and solar irradiation) analysis. It is used to determine location and size of renewable power unit in microgrid planning and operation. Optimisation problem has been designed and applied to the IEEE-13 node distribution system and found best location of wind, solar and microturbine DG for minimisation of network losses, cost and maximum utilisation of natural power sources, . The Particle Swarm optimisation and Levy Flight PSO has been utilised to solve optimisation problem. The Levy PSO is more efficient and gave best solution of proposed method in less time period without trapping.

Bibliography

- [1] European research project microgrids (online).
- [2] Fahad S Abu-Mouti and ME El-Hawary. Optimal distributed generation allocation and sizing in distribution systems via artificial bee colony algorithm. *IEEE transactions on power delivery*, 26(4):2090–2101, 2011.
- [3] Naresh Acharya, Pukar Mahat, and Nadarajah Mithulananthan. An analytical approach for dg allocation in primary distribution network. *International Journal of Electrical Power & Energy Systems*, 28(10):669–678, 2006.
- [4] Shabir Ahmad, Israr Ullah, Faisal Jamil, and DoHyeun Kim. Toward the optimal operation of hybrid renewable energy resources in microgrids. *Energies*, 13(20):5482, 2020.
- [5] MR AlRashidi and MF AlHajri. Optimal planning of multiple distributed generation sources in distribution networks: A new approach. *Energy conversion and management*, 52(11):3301–3308, 2011.
- [6] Seyed Ali Arefifar, Yasser Abdel-Rady I Mohamed, and Tarek HM El-Fouly. Supply-adequacy-based optimal construction of microgrids in smart distribution systems. *IEEE transactions on smart grid*, 3(3):1491–1502, 2012.
- [7] Seyed Ali Arefifar, Martin Ordonez, and Yasser Abdel-Rady I Mohamed. Vi controllability-based optimal allocation of resources in smart distribution systems. *IEEE Transactions on Smart Grid*, 7(3):1378–1388, 2016.
- [8] Juan Camilo Arevalo, Fabian Santos, and Sergio Rivera. Uncertainty cost functions for solar photovoltaic generation, wind energy generation, and plug-in electric vehicles: Mathematical expected value and verification by monte carlo simulation. *International journal of power and energy conversion*, 10(2):171–207, 2019.

- [9] Yarhands Dissou Arthur, Kwasi Baah Gyamfi, and SK Appiah. Probability distributional analysis of hourly solar irradiation in kumasi-ghana. *International Journal of Business and Social Research (IJBSR)*, 3(3), 2013.
- [10] Raji Atia and Noboru Yamada. Sizing and analysis of renewable energy and battery systems in residential microgrids. *IEEE Transactions on Smart Grid*, 7(3):1204–1213, 2016.
- [11] Yasser M Atwa and Ehab F El-Saadany. Probabilistic approach for optimal allocation of wind-based distributed generation in distribution systems. *IET Renewable Power Generation*, 5(1):79–88, 2011.
- [12] Yasser Moustafa Atwa and EF El-Saadany. Optimal allocation of ess in distribution systems with a high penetration of wind energy. *IEEE Transactions on Power Systems*, 25(4):1815–1822, 2010.
- [13] YM Atwa, EF El-Saadany, MMA Salama, and R Seethapathy. Optimal renewable resources mix for distribution system energy loss minimization. *IEEE Transactions on Power Systems*, 25(1):360–370, 2010.
- [14] YM Atwa, Ehab F El-Saadany, MMA Salama, R Seethapathy, M Assam, and S Conti. Adequacy evaluation of distribution system including wind/solar dg during different modes of operation. *IEEE Transactions on Power systems*, 26(4):1945–1952, 2011.
- [15] HS Bagiorgas, MN Assimakopoulos, D Theoharopoulos, D Matthopoulos, and GK Mihalakakou. Electricity generation using wind energy conversion systems in the area of western greece. *Energy Conversion and Management*, 48(5):1640–1655, 2007.
- [16] Binayak Bhandari, Kyung-Tae Lee, Gil-Yong Lee, Young-Man Cho, and Sung-Hoon Ahn. Optimization of hybrid renewable energy power systems: A review. *International journal of precision engineering and manufacturing-green technology*, 2(1):99–112, 2015.
- [17] Suman Bhullar and Smarajit Ghosh. Optimal integration of multi distributed generation sources in radial distribution networks using a hybrid algorithm. *Energies*, 11(3):628, 2018.

- [18] Roy Billinton, Hua Chen, and R Ghajar. Time-series models for reliability evaluation of power systems including wind energy. *Microelectronics Reliability*, 36(9):1253–1261, 1996.
- [19] Suman Biswal, Arnab Ghosh, Sajjan Kumar, Niladri Chakraborty, and Swapan Kumar Goswami. Cuckoo search algorithm based cost minimization by optimal dg and capacitor integration in radial distribution systems. In *2018 20th National Power Systems Conference (NPSC)*, pages 1–6. IEEE, 2018.
- [20] Carmen LT Borges and Djalma M Falcao. Optimal distributed generation allocation for reliability, losses, and voltage improvement. *International Journal of Electrical Power & Energy Systems*, 28(6):413–420, 2006.
- [21] Godfrey Boyle. *Renewable Energy*; Boyle, G., Ed. Oxford University Press: Oxford, UK, 2004.
- [22] FL Camera. Renewable power generation costs in 2018. *International Renewable Energy Agency (IRENA): Abu Dhabi, UAE*, 2019.
- [23] Ali Naci Celik. Energy output estimation for small-scale wind power generators using weibull-representative wind data. *Journal of wind engineering and industrial aerodynamics*, 91(5):693–707, 2003.
- [24] Changsong Chen and Shanxu Duan. Optimal allocation of distributed generation and energy storage system in microgrids. *IET Renewable Power Generation*, 8(6):581–589, 2014.
- [25] Dharmesh Dabhi and Kartik Pandya. Enhanced velocity differential evolutionary particle swarm optimization for optimal scheduling of a distributed energy resources with uncertain scenarios. *IEEE access*, 8:27001–27017, 2020.
- [26] Sabereh Darbandi, Mohammad Taghi Aalami, and Hakimeh Asadi. Comparison of four distributions for frequency analysis of wind speed. *Environment and Natural Resources Research*, 2(1):96, 2012.
- [27] Chris J Dent, Luis F Ochoa, and Gareth P Harrison. Network distributed generation capacity analysis using opf with voltage step constraints. *IEEE Transactions on Power systems*, 25(1):296–304, 2009.
- [28] Maimouna Diagne, Mathieu David, Philippe Lauret, John Boland, and Nicolas Schmutz. Review of solar irradiance forecasting methods and a proposition for

- small-scale insular grids. *Renewable and Sustainable Energy Reviews*, 27:65–76, 2013.
- [29] Guzman Diaz, Ahmed M Abd-el Motaleb, and Veronica Mier. On the capacity factor of distributed wind generation in droop-regulated microgrids. *IEEE Transactions on Power Systems*, 28(2):1738–1746, 2013.
- [30] C Draxl, A Purkayastha, and Z Parker. Wind resource assessment of gujarat (india)(no. nrel/tp-5000–61741). *National Renewable Energy Lab.(NREL), Golden, CO (United States)*, 2014.
- [31] Ali Ehsan and Qiang Yang. Optimal integration and planning of renewable distributed generation in the power distribution networks: A review of analytical techniques. *Applied Energy*, 210:44–59, 2018.
- [32] Walid El-Khattam, YG Hegazy, and MMA Salama. An integrated distributed generation optimization model for distribution system planning. *IEEE transactions on power systems*, 20(2):1158–1165, 2005.
- [33] AM El-Zonkoly. Optimal placement of multi-distributed generation units including different load models using particle swarm optimisation. *IET generation, transmission & distribution*, 5(7):760–771, 2011.
- [34] Mohamed R Elkadeem, Mohamed Abd Elaziz, Zia Ullah, Shaorong Wang, and Swellam W Sharshir. Optimal planning of renewable energy-integrated distribution system considering uncertainties. *IEEE Access*, 7:164887–164907, 2019.
- [35] Masoud Esmaili. Placement of minimum distributed generation units observing power losses and voltage stability with network constraints. *IET Generation, Transmission & Distribution*, 7(8):813–821, 2013.
- [36] Masoud Esmaili, Esmail Chaktan Firozjaee, and Heidar Ali Shayanfar. Optimal placement of distributed generations considering voltage stability and power losses with observing voltage-related constraints. *Applied energy*, 113:1252–1260, 2014.
- [37] Siyao Feng, Wenjun Yin, and Haifeng Wang. Integrated micro-grid optimization and control technology. In *2011 International Conference on Advanced Power System Automation and Protection*, volume 3, pages 2072–2075, 2011.

- [38] Toshihisa Funabashi and Ryuichi Yokoyama. Microgrid field test experiences in japan. In *2006 IEEE Power Engineering Society General Meeting*, pages 2–pp. IEEE, 2006.
- [39] Pavlos S Georgilakis and Nikos D Hatziaargyriou. Optimal distributed generation placement in power distribution networks: models, methods, and future research. *IEEE Transactions on Power Systems*, 28(3):3420–3428, 2013.
- [40] Mahmoud Ghofrani, Amirsaman Arabali, Mehdi Etezadi-Amoli, and Mohammed Sami Fadali. A framework for optimal placement of energy storage units within a power system with high wind penetration. *IEEE Transactions on Sustainable Energy*, 4(2):434–442, 2013.
- [41] Tuba Gözel and M Hakan Hocaoglu. An analytical method for the sizing and siting of distributed generators in radial systems. *Electric power systems research*, 79(6):912–918, 2009.
- [42] A Hadian and M-R Haghifam. Placement of dg with stochastic generation. In *Transmission and Distribution Conference and Exposition, 2010 IEEE PES*, pages 1–7. IEEE, 2010.
- [43] Ryan Hanna, Mohamed Ghonima, Jan Kleissl, George Tynan, and David G Victor. Evaluating business models for microgrids: Interactions of technology and policy. *Energy Policy*, 103:47–61, 2017.
- [44] Yosuke Hariya, Takuya Kurihara, Takuya Shindo, and Kenya Jin’no. Lévy flight pso. In *2015 IEEE Congress on Evolutionary Computation (CEC)*, pages 2678–2684. IEEE, 2015.
- [45] Hamid HassanzadehFard and Alireza Jalilian. Optimal sizing and location of renewable energy based dg units in distribution systems considering load growth. *International Journal of Electrical Power & Energy Systems*, 101:356–370, 2018.
- [46] Adam Hirsch, Yael Parag, and Josep Guerrero. Microgrids: A review of technologies, key drivers, and outstanding issues. *Renewable and sustainable Energy reviews*, 90:402–411, 2018.

- [47] Ying-Yi Hong and Ruo-Chen Lian. Optimal sizing of hybrid wind/pv/diesel generation in a stand-alone power system using markov-based genetic algorithm. *IEEE Transactions on Power Delivery*, 27(2):640–647, 2012.
- [48] SJAD Hosseini, Mohammadreza Moradian, Hossein Shahinzadeh, and Sima Ahmadi. Optimal placement of distributed generators with regard to reliability assessment using virus colony search algorithm. *International Journal of Renewable Energy Research (IJRER)*, 8(2):714–723, 2018.
- [49] Po Hu, Rajesh Karki, and Roy Billinton. Reliability evaluation of generating systems containing wind power and energy storage. *IET generation, transmission & distribution*, 3(8):783–791, 2009.
- [50] Duong Quoc Hung. Smart integration of distributed renewable generation and battery energy storage. 2014.
- [51] Duong Quoc Hung and Nadarajah Mithulananthan. Multiple distributed generator placement in primary distribution networks for loss reduction. *IEEE Transactions on Industrial Electronics*, 60(4):1700–1708, 2013.
- [52] Duong Quoc Hung, Nadarajah Mithulananthan, and RC Bansal. Analytical expressions for dg allocation in primary distribution networks. *IEEE Transactions on energy conversion*, 25(3):814–820, 2010.
- [53] Duong Quoc Hung, Nadarajah Mithulananthan, and RC Bansal. Analytical strategies for renewable distributed generation integration considering energy loss minimization. *Applied Energy*, 105:75–85, 2013.
- [54] Duong Quoc Hung, Nadarajah Mithulananthan, and Kwang Y Lee. Optimal placement of dispatchable and nondispatchable renewable dg units in distribution networks for minimizing energy loss. *International Journal of Electrical Power & Energy Systems*, 55:179–186, 2014.
- [55] KRISTIN IGUSKY, REBECCA GASPER, and NOAH KAUFMAN. How illinois can meet its clean power plan targets. 2016.
- [56] Satish Kumar Injeti, Vinod Kumar Thunuguntla, and Meera Shareef. Optimal allocation of capacitor banks in radial distribution systems for minimization of real power loss and maximization of network savings using bio-inspired

- optimization algorithms. *International Journal of Electrical Power & Energy Systems*, 69:441–455, 2015.
- [57] Rich H Inman, Hugo TC Pedro, and Carlos FM Coimbra. Solar forecasting methods for renewable energy integration. *Progress in energy and combustion science*, 39(6):535–576, 2013.
- [58] R Jensi and G Wiselin Jiji. An enhanced particle swarm optimization with levy flight for global optimization. *Applied Soft Computing*, 43:248–261, 2016.
- [59] Quanyuan Jiang, Meidong Xue, and Guangchao Geng. Energy management of microgrid in grid-connected and stand-alone modes. *IEEE transactions on power systems*, 28(3):3380–3389, 2013.
- [60] Huang Jiayi, Jiang Chuanwen, and Xu Rong. A review on distributed energy resources and microgrid. *Renewable and Sustainable Energy Reviews*, 12(9):2472–2483, December 2008.
- [61] Tongdan Jin, Ying Yu, and Elsayed Elsayed. Reliability and quality control for distributed wind/solar energy integration: a multi-criteria approach. *IIE Transactions*, 47(10):1122–1138, 2015.
- [62] Satish Kansal, Vishal Kumar, and Barjeev Tyagi. Optimal placement of different type of dg sources in distribution networks. *International Journal of Electrical Power & Energy Systems*, 53:752–760, 2013.
- [63] R. Karki and R. Billinton. Cost-effective wind energy utilization for reliable power supply. *IEEE Transactions on Energy Conversion*, 19(2):435–440, 2004.
- [64] Rajesh Karki, Po Hu, and Roy Billinton. A simplified wind power generation model for reliability evaluation. *IEEE transactions on Energy conversion*, 21(2):533–540, 2006.
- [65] F. Katiraei and J. R. Aguero. Solar pv integration challenges. *IEEE Power and Energy Magazine*, 9(3):62–71, May 2011.
- [66] Farid Katiraei, Reza Iravani, Nikos Hatziargyriou, and Aris Dimeas. Microgrids management. *IEEE Power and Energy Magazine*, 6(3):54–65, 2008.
- [67] Andrew Keane and Mark O’Malley. Optimal allocation of embedded generation on distribution networks. *IEEE Transactions on Power Systems*, 20(3):1640–1646, 2005.

- [68] Andrew Keane and Mark O'Malley. Optimal utilization of distribution networks for energy harvesting. *IEEE Transactions on Power Systems*, 22(1):467–475, 2007.
- [69] DNV Kema. Microgrids—benefits, models, barriers and suggested policy initiatives for the commonwealth of massachusetts, 2014.
- [70] William H Kersting. Radial distribution test feeders. *IEEE Transactions on Power Systems*, 6(3):975–985, 1991.
- [71] M. Venkata Kirthiga, S. Arul Daniel, and S. Gurunathan. A methodology for transforming an existing distribution network into a sustainable autonomous micro-grid. *IEEE Transactions on Sustainable Energy*, 4(1):31–41, 2013.
- [72] Sujatha Kotamarty, Sarika Khushalani, and Noel Schulz. Impact of distributed generation on distribution contingency analysis. *Electric Power Systems Research*, 78(9):1537–1545, 2008.
- [73] Ashwani Kumar and Wenzhong Gao. Optimal distributed generation location using mixed integer non-linear programming in hybrid electricity markets. *IET generation, transmission & distribution*, 4(2):281–298, 2010.
- [74] Ken Kuroda, Tomiyasu Ichimura, Hideki Magori, and Ryuichi Yokoyama. A new approach for optimal location and sizing of distributed generation using an exact solution method. *International Journal of Smart Grid and Clean Energy*, 1(1):109–115, 2012.
- [75] R Lasseter, A Akhil, C Marnay, J Stephens, J Dagle, R Guttromson, AS Meliopoulos, R Yinger, and J Eto. White paper on integration of distributed energy resources. the certs microgrid concept, consortium for electric reliability technology solutions (certs). *LBNL-50829. certs. lbl.gov/pdf/50829-apdf (April 2002)*, 2002.
- [76] R.H. Lasseter and P. Paigi. Microgrid: a conceptual solution. In *2004 IEEE 35th Annual Power Electronics Specialists Conference (IEEE Cat. No.04CH37551)*, volume 6, pages 4285–4290 Vol.6, 2004.
- [77] Robert Lasseter, Abbas Akhil, Chris Marnay, John Stephens, Jeff Dagle, Ross Guttromsom, A Sakis Meliopoulos, Robert Yinger, and Joe Eto. Integration

- of distributed energy resources. the certs microgrid concept. Technical report, Lawrence Berkeley National Lab.(LBNL), Berkeley, CA (United States), 2002.
- [78] Robert H Lasseter. Control and design of microgrid components. *PSERC Publication 06-03*, 2006.
- [79] Fernando Lezama, João Soares, Zita Vale, Jose Rueda, Sergio Rivera, and István Elrich. 2017 iee competition on modern heuristic optimizers for smart grid operation: Testbeds and results. *Swarm and evolutionary computation*, 44:420–427, 2019.
- [80] Zhiyong Li, Weiyou Wang, Yanyan Yan, and Zheng Li. Ps-abc: A hybrid algorithm based on particle swarm and artificial bee colony for high-dimensional optimization problems. *Expert Systems with Applications*, 42(22):8881–8895, 2015.
- [81] Zhipeng Liu, Fushuan Wen, and Gerard Ledwich. Optimal siting and sizing of distributed generators in distribution systems considering uncertainties. *IEEE Transactions on power delivery*, 26(4):2541–2551, 2011.
- [82] Munish Manas et al. Renewable energy management through microgrid central controller design: An approach to integrate solar, wind and biomass with battery. *Energy reports*, 1:156–163, 2015.
- [83] Eric Martinot et al. *Renewables 2015: Global status report*. 2015.
- [84] Gilbert M Masters. *Renewable and efficient electric power systems*. John Wiley & Sons, 2013.
- [85] Avirup Maulik and Debapriya Das. Optimal operation of microgrid using four different optimization techniques. *Sustainable Energy Technologies and Assessments*, 21:100–120, 2017.
- [86] Avirup Maulik and Debapriya Das. Optimal power dispatch considering load and renewable generation uncertainties in an ac-dc hybrid microgrid. *IET Generation, Transmission & Distribution*, 13(7):1164–1176, 2019.
- [87] Vladimiro Miranda and Rui Alves. Differential evolutionary particle swarm optimization (deepso): A successful hybrid. In *2013 BRICS Congress on Computational Intelligence and 11th Brazilian Congress on Computational Intelligence*, pages 368–374. IEEE, 2013.

- [88] MH Moradi and M Abedini. A combination of genetic algorithm and particle swarm optimization for optimal distributed generation location and sizing in distribution systems with fuzzy optimal theory. *International Journal of Green Energy*, 9(7):641–660, 2012.
- [89] MH Moradi and M Abedini. A novel method for optimal dg units capacity and location in microgrids. *International Journal of Electrical Power & Energy Systems*, 75:236–244, 2016.
- [90] Mohammad Hasan Moradi and M Abedini. A combination of genetic algorithm and particle swarm optimization for optimal dg location and sizing in distribution systems. *International Journal of Electrical Power & Energy Systems*, 34(1):66–74, 2012.
- [91] Ali Mostafaeipour, Mohsen Jadidi, Kasra Mohammadi, and Ahmad Sedaghat. An analysis of wind energy potential and economic evaluation in zahedan, iran. *Renewable and Sustainable Energy Reviews*, 30:641–650, 2014.
- [92] Arash Navaeefard, S. M. Moghaddas Tafreshi, Mostafa Barzegari, and Amir Jalali Shahrood. Optimal sizing of distributed energy resources in micro-grid considering wind energy uncertainty with respect to reliability. In *2010 IEEE International Energy Conference*, pages 820–825, 2010.
- [93] Arash Navaeefard, SM Moghaddas Tafreshi, Mostafa Barzegari, and Amir Jalali Shahrood. Optimal sizing of distributed energy resources in micro-grid considering wind energy uncertainty with respect to reliability. In *2010 IEEE International Energy Conference*, pages 820–825. IEEE, 2010.
- [94] Tri Phuoc Nguyen, Dieu Ngoc Vo, et al. Optimal number, location, and size of distributed generators in distribution systems by symbiotic organism search based method. *Advances in Electrical and Electronic Engineering*, 15(5):724–735, 2018.
- [95] Luis F Ochoa, Chris J Dent, and Gareth P Harrison. Distribution network capacity assessment: Variable dg and active networks. *IEEE Transactions on Power Systems*, 25(1):87–95, 2009.

- [96] Luis F Ochoa and Gareth P Harrison. Minimizing energy losses: Optimal accommodation and smart operation of renewable distributed generation. *IEEE Transactions on Power Systems*, 26(1):198–205, 2010.
- [97] V Ravikumar Pandi, HH Zeineldin, and Weidong Xiao. Determining optimal location and size of distributed generation resources considering harmonic and protection coordination limits. *IEEE transactions on power systems*, 28(2):1245–1254, 2012.
- [98] Pierre Pinson. Very-short-term probabilistic forecasting of wind power with generalized logit-normal distributions. *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, 61(4):555–576, 2012.
- [99] S Porkar, P Poure, A Abbaspour-Tehrani-fard, and S Saadate. Optimal allocation of distributed generation using a two-stage multi-objective mixed-integer-nonlinear programming. *European Transactions on Electrical Power*, 21(1):1072–1087, 2011.
- [100] W Prommee and W Ongsakul. Optimal multiple distributed generation placement in microgrid system by improved reinitialized social structures particle swarm optimization. *European Transactions on Electrical Power*, 21(1):489–504, 2011.
- [101] Lea Ranalder, Henner Busch, Teis Hansen, Marit Brommer, Toby Couture, Duncan Gibb, Flávia Guerra, Joel Nana, Yachika Reddy, Janet Sawin, et al. Renewables in cities 2021 global status report. In *REN21 Secretariat*. 2021.
- [102] R Srinivasa Rao, Kumudhini Ravindra, K Satish, and SVL Narasimham. Power loss minimization in distribution system using network reconfiguration in the presence of distributed generation. *IEEE transactions on power systems*, 28(1):317–325, 2012.
- [103] Sergio Rivera, Aameena Saad Al-Sumaiti, Camilo Cortes, José Rueda, Kwang Y Lee, and István Erlich. 2018 grid optimization competition.
- [104] K Santhosh and R Neela. Optimal placement of distribution generation in micro-grid using eagle strategy with particle swarm optimizer. *International Journal of Pure and Applied Mathematics*, 118(18):3819–3825, 2018.

- [105] F Daniel Santillán-Lemus, Hertwin Minor-Popocatl, Omar Aguilar-Mejía, and Ruben Tapia-Olvera. Optimal economic dispatch in microgrids with renewable energy sources. *Energies*, 12(1):181, 2019.
- [106] TN Shukla, SP Singh, V Srinivasarao, and KB Naik. Optimal sizing of distributed generation placed on radial distribution systems. *Electric power components and systems*, 38(3):260–274, 2010.
- [107] M. G. Simoes, R. Roche, E. Kyriakides, S. Suryanarayanan, B. Blunier, K. D. McBee, P. H. Nguyen, P. F. Ribeiro, and A. Miraoui. A comparison of smart grid technologies and progresses in europe and the u.s. *IEEE Transactions on Industry Applications*, 48(4):1154–1162, July 2012.
- [108] Deependra Singh, Devender Singh, and KS2597632 Verma. Multiobjective optimization for dg planning with load models. *IEEE transactions on power systems*, 24(1):427–436, 2009.
- [109] RK Singh and SK Goswami. Optimal siting and sizing of distributed generations in radial and networked systems considering different voltage dependent static load models. In *2008 IEEE 2nd International Power and Energy Conference*, pages 1535–1540. IEEE, 2008.
- [110] RK Singh and SK Goswami. Optimum siting and sizing of distributed generations in radial and networked systems. *Electric Power Components and Systems*, 37(2):127–145, 2009.
- [111] J Sneha, K Kumar, V Bens Joie Victor, and J Aran Glenn. Optimal placement of different types of dg sources in distribution networks using pso algorithm and differential evolution. *IOSR Journal of Electrical and Electronics Engineering (IOSR-JEEE) e-ISSN*, pages 2278–1676, 2014.
- [112] João Soares, Cristina Lobo, Marco Silva, Hugo Morais, and Zita Vale. Relaxation of non-convex problem as an initial solution of meta-heuristics for energy resource management. In *2015 IEEE Power & Energy Society General Meeting*, pages 1–5. IEEE, 2015.
- [113] Alireza Soroudi, Morteza Aien, and Mehdi Ehsan. A probabilistic modeling of photo voltaic modules and wind power generation impact on distribution networks. *IEEE Systems Journal*, 6(2):254–259, 2011.

- [114] Probability Methods Subcommittee. Ieee reliability test system. *IEEE Transactions on power apparatus and systems*, (6):2047–2054, 1979.
- [115] Mohamed A. Tolba, Vladimir N. Tulskey, and Ahmed A. Zaki Diab. Optimal allocation and sizing of multiple distributed generators in distribution networks using a novel hybrid particle swarm optimization algorithm. In *2017 IEEE Conference of Russian Young Researchers in Electrical and Electronic Engineering (EIConRus)*, pages 1606–1612, 2017.
- [116] Rajkumar Viral and DK Khatod. Optimal planning of distributed generation systems in distribution system: A review. *Renewable and Sustainable Energy Reviews*, 16(7):5146–5165, 2012.
- [117] Lingfeng Wang and Chanan Singh. Reliability-constrained optimum placement of reclosers and distributed generators in distribution networks using an ant colony system algorithm. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 38(6):757–764, 2008.
- [118] Zhaoyu Wang, Bokan Chen, Jianhui Wang, and Miroslav M Begovic. Stochastic dg placement for conservation voltage reduction based on multiple replications procedure. *IEEE Transactions on Power Delivery*, 30(3):1039–1047, 2015.
- [119] Zhaoyu Wang, Bokan Chen, Jianhui Wang, and Miroslav M. Begovic. Stochastic dg placement for conservation voltage reduction based on multiple replications procedure. *IEEE Transactions on Power Delivery*, 30(3):1039–1047, 2015.
- [120] Shengxuan Wei, Qianjin Liu, et al. Review of modeling methods of distributed energy supply system connected to the grid. *Energy and Power Engineering*, 5(04):1317, 2013.
- [121] H Lee Willis. Analytical methods and rules of thumb for modeling dg-distribution interaction. In *2000 power engineering society summer meeting (Cat. No. 00CH37134)*, volume 3, pages 1643–1644. IEEE, 2000.
- [122] Ting Wu, Qiang Yang, Zhejing Bao, and Wenjun Yan. Coordinated energy dispatching in microgrid with wind power generation and plug-in electric vehicles. *IEEE Transactions on Smart Grid*, 4(3):1453–1463, 2013.

- [123] Muhammad Yousif, Qian Ai, Yang Gao, Waqas Ahmad Wattoo, Ziqing Jiang, and Ran Hao. Application of particle swarm optimization to a scheduling strategy for microgrids coupled with natural gas networks. *Energies*, 11(12):3499, 2018.
- [124] Yao Zhang, Jianxue Wang, and Xifan Wang. Review on probabilistic forecasting of wind power generation. *Renewable and Sustainable Energy Reviews*, 32:255–270, 2014.
- [125] Yongxi Zhang, Zhao Yang Dong, Fengji Luo, Yu Zheng, Ke Meng, and Kit Po Wong. Optimal allocation of battery energy storage systems in distribution networks with high wind power penetration. *IET Renewable Power Generation*, 10(8):1105–1113, 2016.
- [126] Yu Zheng, Zhao Yang Dong, Feng Ji Luo, Ke Meng, Jing Qiu, and Kit Po Wong. Optimal allocation of energy storage system for risk mitigation of discos with high renewable penetrations. *IEEE Transactions on Power Systems*, 29(1):212–220, 2013.
- [127] Dan Zhu, Robert P Broadwater, Kwa-Sur Tam, Rich Seguin, and Haukur Asgeirsson. Impact of dg placement on reliability and efficiency with time-varying loads. *IEEE Transactions on Power Systems*, 21(1):419–427, 2006.