List of Figures

. .

,

| Fig. No | Figure Details | Page No |
|---------|--|---------|
| | Chapter I | |
| 1.1 | Block representation of Ideal AC-AC converter | 2 |
| 1.2 | A pictorial View of Motor Generator Set | 3 |
| 1.3 | Pulse-width modulated voltage source inverter | 4 |
| 1.4 | Direct AC-AC converters | 6 |
| 1.5 | a. Single half bridge ac power controllerb. Single Phase Full Bridge AC power controller | 7 |
| 1.6 | Output Waveforms voltage and current waveforms of Single Phase Full Bridge AC power controller | 8 |
| 1.7 | a. Configuration of single-phase ac chopperb. Output voltage and load current waveforms | 8 9 |
| 1.8 | a. Three phase ac power controller with WYE connection | 10 |
| 1.9 | b. Delta connection configurations. General representation of Cycloconverter | 10 |
| 1.9 | Single-phase full bridge cycloconverters | 10 |
| 1.10 | Single-phase to single-phase cycloconverter waveforms | 12 |
| 1.12 | a. Input voltage b. Output voltage for zero firing angle c. Output voltage with firing angle □/3 rad. d. Output voltage with varying firing angle 3\$\phi-1\$\phi Half bridge cycloconverter | 14 |
| 1.13 | 3 ϕ -1 ϕ Full bridge cycloconverter | 14 |
| 1.14 | 3□-1□half-wave cycloconverter waveforms a.+ Converter output voltage b.Cosine timing waves c Converter output voltage | 15 |
| 1.15 | 3□-3□half-wave cycloconverter | 16 |
| 1.16 | 3□-3□half-wave cycloconverter | 17 |
| 1.17 | Block representation of voltage source inverters | 21 |
| 1.18 | Active filter topology for compensation of harmonic currents | 22 |
| 1.19 | Matrix converter | 23 |
| | Chapter II | |
| 2.1 | Generalized structure of static transformer | 30 |
| 2.2 | Circuit scheme of a three phase to three-phase matrix converter, where a, b, c are at the input terminals and A, B, C are at the output terminals. | 31 |

.

| 2.3 | Switching constraints Short circuit between input phases | 32 |
|-------|--|----------|
| 2.4 | Open circuit for output phase Bi-directional switch configuration | 34 |
| 2.5 | Typical waveforms for a relatively low switching frequency are | 37 |
| 2.6 | shown in figure above Equivalent model of matrix converter for indirect mode operation | 42 |
| 2.0 | a. Input voltages, functions F1, F2 & F3, output | 45 |
| 2.8 | voltage V_{AB} b. Gate pulses for Bidirectional switches Simultaneous turning on operation leading to short circuit and turning off of two switches leading to high voltages due to | 46 47 |
| • • | breaking of inductive currents | |
| 2.9 | Bidirectional Switch | 48 |
| 2.10 | Matrix converter with two-phase grid and single-phase load | 49 |
| 2.11 | State diagram of the soft-switching commutation method: a. For positive load current; | 50 |
| 2.12 | b. General case, i.e. load current of any polarity. Schematic representation of a matrix converter adjustable speed drive | 51 |
| 2.13 | Basic input filter configurations used in matrix converter prototypes. | 52 |
| 2.14 | Clamp circuit as common protection for all matrix converter bi- directional switches. | 55 |
| 2.15. | Matrix converter with varistor protection | 56 |
| 2.16 | Gate driver with suppressor protection. | 58 |
| 2.17 | Output voltage waveforms generated by a VSI and a matrix converter | 59 |
| 2.18 | Matrix converter input current and harmonic spectrum. Switching frequency 2kHz. | 60 |
| 2.19 | Matrix converter input line-to-neutral voltage, instantaneous input current and its average value | 61 |
| 2.20 | Three-phase to single-phase full bridge Direct AC-AC converter | 70 |
| 2.21 | Three-phase to single-phase half bridge Direct AC-AC converter | 71 |
| 2.22 | Single-phase to three-phase ARNO converter | 75 |
| 2.23 | Single-phase to three-phase static converter using auto transformer | 76 |
| 2.24 | Single-phase to three-phase static converter using IGBT bridge | 77 |
| | Chapter III | |
| 3.1 | Three-phase to three-phase high frequency generator | 83 |
| 3.2 | Simplified power circuit diagram for the three-phase to single- phase direct high frequency AC-AC converter (half bridge configuration) | 84 |
| 3.3 | Simplified power circuit diagram for the three-phase to single- phase direct high frequency AC-AC converter (full bridge | 84 |
| | | ix |

| `` | configuration) | |
|------|--|-----|
| 3.4 | Modeling of bidirectional switch using two IGBTs with two anti- parallel diodes | 89 |
| 3.5 | The proposed Direct AC-AC high frequency link converter | 90 |
| 3.6 | The modified Direct AC-AC high frequency link converter | 90 |
| 3.7 | Waveforms of input phase voltages and its division into six sectors | 92 |
| 3.8 | Equivalent circuit diagram for sector one when $S_{yn} \& S_{bp}$ are conducting | 96 |
| 3.9 | Equivalent circuit diagram for sector one when $S_{yn} \& S_{rp}$ are conducting | 96 |
| 3.10 | Equivalent circuit diagram for sector one when $S_{yp} \& S_{bn}$ are conducting | 97 |
| 3.11 | Equivalent circuit diagram for sector one when $S_{yp} \& S_m$ are conducting | 97 |
| 3.12 | A simplified transformer design | 99 |
| 3.13 | The ideal transformer as a circuit element | 100 |
| 3.14 | Three-phase inverter circuit | 103 |
| 3.15 | Block Diagram of three-phase inverter with SPWM technique | 105 |
| 3.16 | Principle of pulse generation using SPWM technique | 105 |
| 3.17 | Inverter reference signal; output voltage V_{ab} ; harmonic spectrum of V_{ab} | 106 |
| 3.18 | Three-phase inverter with R-L-E load | 107 |
| 3.19 | Equivalent inverter circuit during various switching states | 109 |
| 3.20 | The relationship of abc reference frame and stationary dq reference frame. | 109 |
| 3.21 | Basic switching vectors and sectors. | 111 |
| 3.22 | Voltage Space Vector and its components in (d, q) | 112 |
| 3.23 | Reference vector as a combination of adjacent vectors at sector 1. | 114 |
| 3.24 | Space Vector PWM switching patterns at each sector | 115 |
| | Chapter IV | |
| 4.1 | Control block diagram for Direct AC-AC conversion | 129 |
| 4.2 | Absolute instantaneous value of three phase voltages | 130 |
| 4.3 | Zero crossing detector waveforms | 130 |
| 4.4 | Sector detection for all the phases | 131 |
| 4.5 | Sector detection for R-phase (positive and negative half cycles) | 131 |
| 4.6 | Divider Circuit using multiplier IC and opamps | 133 |
| 4.7 | Modulation function for all three phases | 133 |
| 4.8 | Positive and negative ramp generating circuit | 134 |
| 4.9 | Positive and negative slope ramps | 134 |

х

| 4.10 | Pictorial View of Analog circuits based control cards a. Sector determination and ZCD card b. Divider card and duty cycle calculation card c. Ramp generation card | 135 | |
|------------|---|------|----|
| 4.11 | d. Digital card for gate pulses Pictorial view of setup for all control cards inter connected to one another | 136 | |
| 4.12 | Pictorial view of the DSP based control board | 143 | |
| 4.13 | Pictorial view of the analog based complete set-up | 144 | |
| 4.14 | Pictorial view of the DSP based complete set-up | 145 | |
| 4.15 | Output of the high frequency transformer. | 145 | |
| 4.16 | a. Input voltages and the input current without input ripple filter | 146 | |
| | b. Input voltages and the input current with input ripple filter | 146 | |
| 4.17 | Output line voltage for R-Y voltage | 146 | •, |
| 4.18 | Output phase R-N voltage | 147 | |
| | Chapter V | | |
| 5.1 | Three-phase to three-phase direct AC-AC converter | 150 | |
| 5.2 | Block model of Direct AC-AC converter using IMO mode | 151 | |
| 5.3 | Topology with 18 unidirectional voltage blocking switches | 152 | |
| 5.4 | Topology with 12 unidirectional voltage blocking switches | 152 | |
| 5.5 | Topology with 9 unidirectional voltage blocking switches | 153 | |
| 5.6 | Input sine waveforms and sector calculation | 154 | |
| 5.7 | Equivalent circuit during mode 1 of line side converter during interval 1 | 155 | |
| 5.8 | Equivalent circuit during mode 2 of line side converter during interval 1 | 155 | |
| 5.9 | Fully rectified waveforms of Three-Phase to Neutral voltages | 165 | |
| 5.10 | Sector determination for all the three phases for primary side converter | 165 | |
| 5.11 | Gate pulses for all three IGBTs of the primary side converter | 166 | |
| 5.12 | Intermediate DC voltage and current | 167 | |
| 5.13 | Input voltage and input current for one phase | 167 | |
| <i>.</i> . | Chapter VI | 1.60 | |
| 6.1 | Conventional telecommunication switch mode power supply | 168 | |
| 6.2 | Proposed digitally controlled switch mode power supply based on matrix converter. | 169 | |
| 6.3 | Semikron make 2-IGBT switch module for matrix converter implementation | 170 | |
| 6.4 | A figure of three-phase to single phase matrix converter. | 171 | |
| 6.5 | Illustration of matrix converter operation | 171 | |
| | | | |

| 6.6 | Rectifier space vector hexagon. | 173 |
|------|---|-----|
| 6.7 | Inverter mode switching function. | 174 |
| 6.8 | Block diagram of the proposed matrix converter modulation. | 176 |
| 6.9 | Matrix converter switch gating signals generating through logic gates. | 176 |
| 6.10 | The three-phase input voltages V_{ab} , V_{bc} , and V_{ca} : 208 V (rms) 60 Hz. | 179 |
| 6.11 | High frequency output voltage pri V of the matrix converter. | 189 |
| 6.12 | Output DC voltage (48 V). | 180 |
| 6.13 | Input line to neutral input voltage V_{an} and input current I_a . | 180 |
| 6.14 | THD percentage at different loads | 181 |
| 6.15 | Proposed matrix converter prototype | 182 |
| 6.16 | Input voltage V_{ab} , matrix converter output voltage V_{pri} , and transformer secondary voltage V_{sec} . | 182 |
| 6.17 | Transformer primary Vpri and secondary voltages Vsec | 183 |
| 6.18 | Output DC voltage V_{dc} and load current I_{dc} . | 183 |
| 6.19 | Input line to neutral voltage an V and the input line current $a I$ at 1.5 kW of output power | 184 |
| 6.20 | Development of power and size of wind turbines at market introduction | 185 |
| 6.21 | Schematic of connection of DFIM to the grid using AC-AC converter | 187 |
| 6.22 | Block of Control of DFIM using Direct AC-AC converter | 190 |
| 6.23 | Active and Reactive power flow in DFIG | 192 |
| 6.24 | Turbine characteristics and tracking characteristic | 193 |
| 6.25 | Rotor-side and grid-side converters and control systems a. Rotor and Grid side converters b. Rotor side controller c. Grid side controller | 194 |
| 6.26 | V-I characteristics of a Wind Turbine | 195 |

.

.

۰.

xii