

# List of figures

---

Figure 1-1 Schematic of experimental set-up [4] .....	1
Figure 1-2 Classification of WPT techniques.....	2
Figure 1-3 History of electric vehicle.....	9
Figure 2-1 Two coil structure.....	15
Figure 2-2 Dynamic charging systems with one coil design for primary coil $L_1$ = track conductor; $L_2$ = receiver coils; $M$ = mutual inductance between $L_1$ and $L_2$ ; $i_1$ = excitation for primary coil [27,30]. .....	16
Figure 2-3 Dynamic charging systems with segmented-coil design for primary coil [27,30].	16
Figure 2-4 Coil with fixture. $L_{int}$ = intermediate structure; $L_1$ = primary coil structure; $L_2$ = secondary coil structure [23].....	17
Figure 2-5 Different types of coil structures [104-106] .....	18
Figure 2-6 Compensation topologies: (a) SS, (b) SP, (c) PS, and (d) PP. ....	20
Figure 2-7 Two-sided LCC compensation.....	21
Figure 3-1 Biot-Savart Law.....	33
Figure 3-2 Coil spacing.....	34
Figure 3-3 Mutual induction.....	35
Figure 3-4 Block diagram.....	36
Figure 3-5 ANSYS Twinbuilder circuit and relevant waveforms.....	36
Figure 3-6 Frequency vs efficiency graph.....	37
Figure 3-7 Helix coil.....	40
Figure 3-8 Circular coil (theoretical).....	41
Figure 3-9 Design list parameters.....	44
Figure 3-10 Design list: Region & Coils.....	44
Figure 3-11 Circular coil ANSYS top view.....	45
Figure 3-12 ANSYS isometric view.....	45
Figure 3-13 Square coil dimensions.....	46
Figure 3-14 ANSYS model of planner square coil.....	47
Figure 4-1 Magnetic flux lines of helix coil[ 7].....	50
Figure 4-2 Variation of $L$ & $M$ with number of turns for helix coil [7] .....	50
Figure 4-3 Coupling coefficient vs. no. of turns .....	51

---

<i>Figure 4-4 Variation of k with z axis misalignment for helix and spiral coils .....</i>	51
<i>Figure 4-5 Design model of transmitting and receiving coil in ANSYS Electronics Desktop at ZDist of 5 mm.....</i>	52
<i>Figure 4-6 Design model of transmitting and receiving coil in ANSYS Electronics Desktop at ZDist of 150 mm.....</i>	52
<i>Figure 4-7 2D plot showing variation of k with ZDist (I = 10 &amp; 20 Amps).....</i>	53
<i>Figure 4-8 2D plot showing variation of k with ZDist (I = 10 &amp; I induced = 20 Amps) .....</i>	56
<i>Figure 4-9 Plot showing variation of k with ZDist as a function YDist .....</i>	56
<i>Figure 4-10 ZDist v/s k for 0 &amp; 10 A.....</i>	61
<i>Figure 4-11 3D image showing variation of coupling co-efficient v/s YDist and v/s ZDist....</i>	61
<i>Figure 4-12 Contour of coupling co-efficient for YDist and ZDist .....</i>	62
<i>Figure 4-13 Plot of <math>L_1</math> v/s ZDist, <math>L_2</math> v/s ZDist &amp; <math>M_{12}</math> v/s ZDist (0 Amp &amp; 10 Amps) .....</i>	63
<i>Figure 4-14 2D contour of variation between mutual inductance, YDist and ZDist.....</i>	64
<i>Figure 4-15 Flux density at ZDist = 30 mm. ....</i>	66
<i>Figure 4-16 Flux density vector at ZDist=30mm. ....</i>	67
<i>Figure 4-17 Flux density vector ZDist=30 mm and plate at 35 mm .....</i>	67
<i>Figure 4-18 Flux density vector ZDist=30 mm and plate at 15 mm. ....</i>	68
<i>Figure 4-19 Flux density vector ZDist = 30 mm and plate at 15 mm top view.....</i>	68
<i>Figure 4-20 Flux density distribution at ZDist = 55 mm &amp; plate 20 mm.....</i>	69
<i>Figure 4-21 Flux density distribution at ZDist = 55 mm &amp; plate 30 mm.....</i>	69
<i>Figure 4-22 Flux density distribution at ZDist = 55 mm &amp; plate 55 mm.....</i>	69
<i>Figure 4-23 Circular coil configuration at ZDist = 5 mm .....</i>	70
<i>Figure 4-24 Variation of coupling coefficient with respect to ZDist for circular coil .....</i>	72
<i>Figure 4-25 Variation between self and mutual inductance with ZDist for Circular coil .....</i>	72
<i>Figure 4-26 Vertical misalignment of 5 mm and y axis misalignment of 0 mm .....</i>	73
<i>Figure 4-27 Plot showing variation of k with ZDist as a function YDist .....</i>	73
<i>Figure 4-28 Value of k v/s YDist as a function of ZDist. ....</i>	73
<i>Figure 4-29 Value of M v/s YDist as a function of ZDist.....</i>	74
<i>Figure 4-30 Flux density distribution around circular coils. ....</i>	75
<i>Figure 4-31 Flux density distribution around circular coils with less density setting. ....</i>	75
<i>Figure 4-32 Flux density distribution around circular coils in cloud form. ....</i>	75
<i>Figure 4-33 3D plot between f, ZDist and amplitude. ....</i>	76
<i>Figure 4-34 Comparative graph between ZDist vs Coupling coefficient. ....</i>	77

<i>Figure 4-35 ANSYS Twin Builder simulation model.</i> .....	78
<i>Figure 4-36 Power plot.</i> .....	79
<i>Figure 4-37 ANSYS Twin Builder circuit for circular geometry.</i> .....	79
<i>Figure 4-38 Power plot for square coils.</i> .....	81
<i>Figure 4-39 Comparison of efficiencies for square and circular coils.</i> .....	81
<i>Figure 5-1 Block diagram of wireless power transmission for electric vehicle.</i> .....	84
<i>Figure 5-2 System architecture and voltage waveforms.</i> .....	85
<i>Figure 5-3 Flow chart to generate PWM</i> .....	89
<i>Figure 5-4 Hardware prototype.</i> .....	92
<i>Figure 6-1 Complementary gate signals at microcontroller.</i> .....	95
<i>Figure 6-2 Control signal at input terminal of opto-coupler.</i> .....	95
<i>Figure 6-3 Control signal at output terminal of opto-coupler.</i> .....	96
<i>Figure 6-4 Complementary gate pulses at MOSFET driver IRS2110 outputs.</i> .....	96
<i>Figure 6-5 Inverter output voltage</i> .....	97
<i>Figure 6-6 Output voltage across secondary coil</i> .....	98
<i>Figure 6-7 Output voltage waveform across load.</i> .....	98
<i>Figure 6-8 Efficiency plot</i> .....	99
<i>Figure 0-1 Pinout of AT32A.</i> .....	105
<i>Figure 0-2 Opto-isolator circuit.</i> .....	106
<i>Figure 0-3 Opto-coupler circuit.</i> .....	106
<i>Figure 0-4 Circuit diagram of MOSFET driver circuit of sub-module.</i> .....	107
<i>Figure 0-5 Circuit diagram for level shifter/ current gain circuit.</i> .....	108
<i>Figure 0-6 Schematic diagram of resonant inductive power transfer.</i> .....	109