

## List of Figures

<b>Figure 1:</b>	Design composition space of the composites (wt%), excluding rare earth components La and Ce; Binary composites (filled blue circles), Ternary composites (open red circles), Quaternary composites (filled red circles).....	29
<b>Figure 2:</b>	BET-specific surface area of composites calcined at 650°C And hydrothermally aged at 750°C.....	34
<b>Figure 3:</b>	The trend of change in the specific surface area of ternary Al-Mg and Al-Zr supports relative to arithmetic mean of the Binaries.....	35
<b>Figure 4:</b>	Relation between BET-specific surface area and alumina content of the support.....	36
<b>Figure 5:</b>	Percentage Loss of specific surface area for various supports after Hydrothermal treatment.....	37
<b>Figure 6:</b>	Pore volume of composites calcined at 650°C.....	39
<b>Figure 7:</b>	Percentage decrease in pore volume after hydrothermal aging of the supports.....	40
<b>Figure 8:</b>	Median pore diameter of composites calcined at 650°C.....	41
<b>Figure 9:</b>	Median pore diameter (MPDA) of the supports upon hydrothermal aging.....	42
<b>Figure 10:</b>	Pore Diameter Distribution of composites calcined at 650°C.....	42
<b>Figure 11:</b>	Isotherms representative of composites i) not containing alumina; ii) containing alumina.....	43
<b>Figure 12:</b>	Temperature maxima in NH <sub>3</sub> -TPD of composites calcined at 650°C.....	44
<b>Figure 13:</b>	Total acidity and the ratio of strong: weak acidity by NH <sub>3</sub> -TPD.....	46
<b>Figure 14:</b>	Crystallite growth upon hydrothermal aging of composites at 750°C, 4 hours.....	49
<b>Figure 15:</b>	Oxygen storage capacity (OSC) of composites calcined at 650°C.....	53
<b>Figure 16:</b>	Trend of weight loss in DSC-TG of composites dried at 120°C.....	55

<b>Figure 17(a):</b> MBOH conversion trend of binary composites calcined at 650°C.....	60
<b>Figure 17(b):</b> MBOH conversion trend of ternary composites calcined at 650°C.....	61
<b>Figure 17(c):</b> MBOH conversion trend of quaternary composites calcined at 650°C.....	61
<b>Figure 18(a):</b> Selectivity of binary composites to acetone.....	62
<b>Figure 18(b):</b> Selectivity of ternary composites to acetone and acetylene.....	63
<b>Figure 18(c):</b> Selectivity of quaternary composites to acetone and acetylene.....	63
<b>Figure 18(d):</b> Trend of average selectivity to acetone of all the composite samples.....	64
<b>Figure 19(a):</b> Selectivity of binary composites to Mbyne.....	65
<b>Figure 19(b):</b> Selectivity of ternary composites to Mbyne.....	66
<b>Figure 19 (c):</b> Selectivity of quaternary composites to Mbyne.....	67
<b>Figure 19 (d):</b> Average selectivity of all the composites to Mbyne.....	68
<b>Figure 20:</b> Average selectivity of all the composites to MiPK.....	69
<b>Figure 21:</b> Decay constants of composites for decomposition of MBOH.....	70
<b>Figure 22:</b> Fractional molar compositions of composites plotted as increasing deactivation along X axis.....	71
<b>Figure 23:</b> Comparison of BET-specific surface area of the Nickel catalysts and corresponding support.....	83
<b>Figure 24:</b> Change in BET-specific surface area with Nickel content of the catalyst.....	85
<b>Figure 25:</b> Pore volumes of supported Nickel metal-based catalysts.....	86
<b>Figure 26:</b> Change in the specific pore volume of the catalysts with Nickel content of the catalyst.....	87
<b>Figure 27:</b> Trend of strong acidity of the catalysts and the corresponding supports used to prepare them.....	88
<b>Figure 28:</b> Trend of total acidity of supported Nickel catalysts and their corresponding supports.....	90

<b>Figure 29:</b>	Trend of the acid strength of the supported Nickel catalysts.....	91
<b>Figure 30:</b>	Peak maxima of low and high-temperature peaks in TPR of supported Nickel metal catalysts.....	94
<b>Figure 31:</b>	Total H <sub>2</sub> consumption with the breakup of consumption at low and high temperatures.....	99
<b>Figure 32:</b>	Fractional reducibility of NiO of the supported metal catalysts.....	101
<b>Figure 33(a):</b>	XRD pattern of 7.5%Ni-AMZ-0-89-0.....	103
<b>Figure 33(b):</b>	XRD pattern of 7.5%Ni-AMZ-89-0-0 .....	103
<b>Figure 33(c):</b>	XRD pattern of 7.5%Ni-AMZ-0-0-89.....	103
<b>Figure 34:</b>	Specific surface area of Nickel in the supported metal catalysts.....	105
<b>Figure 35:</b>	Trend of the specific surface area of Nickel versus BET surface area of support used for the preparation of the catalysts.....	107
<b>Figure 36:</b>	Trend of the specific surface area of Nickel versus BET surface area of support used for the preparation of the catalyst with constant Nickel content (7.5wt%).....	108
<b>Figure 37:</b>	Dispersion of Nickel as a function of monolayer capacity relative to Nickel content per gram catalyst.....	109
<b>Figure 38:</b>	Correlation of Nickel metal area with BET surface area for catalysts with 7.5wt% and with Nickel reducibility >87%.....	109
<b>Figure 39:</b>	Trend of the specific surface area of Nickel metal with the degree of reducibility of NiO.....	110
<b>Figure 40:</b>	Trend of Nickel metal surface area versus the degree of Nickel Reducibility.....	111
<b>Figure 41:</b>	Trend of crystallite size of NiO and BET-specific surface area with the composition of the support.....	112
<b>Figure 42:</b>	Relation between XRD CS of NiO and median particle size determined by HRTEM.....	115
<b>Figure 43:</b>	Micrograph of binary Al catalyst 7.5%Ni-AMZ-89-0-0.....	117
<b>Figure 44:</b>	Micrograph of binary Mg catalyst 7.5%Ni-AMZ-0-89-0.....	117
<b>Figure 45:</b>	Micrograph of binary Zr catalyst 7.5%Ni-AMZ-0-0-89.....	118

<b>Figure 46:</b>	Micrograph of ternary Al-Mg catalyst 7.5%Ni-AMZ-44-44-0.....	118
<b>Figure 47:</b>	Micrograph of ternary Al-Mg catalyst 7.5%Ni-AMZ-29-59-0.....	119
<b>Figure 48:</b>	Micrograph of ternary Al-Zr catalyst with balanced composition 7.5%Ni-AMZ-44-0-44.....	120
<b>Figure 49:</b>	Micrograph of ternary Al-Zr catalyst with a balanced composition 7.5%Ni-AMZ-39-0-49.....	121
<b>Figure 50:</b>	Micrograph of ternary Al-Zr catalyst with a balanced composition 7.5%Ni-AMZ-29-0-59.....	121
<b>Figure 51:</b>	Micrograph of ternary Mg-Zr catalyst with a balanced composition 7.5%Ni-AMZ-0-44-44.....	122
<b>Figure 52:</b>	Micrograph of the quaternary Al-rich catalyst 7.5%Ni-AMZ-44-22-22.....	123
<b>Figure 53:</b>	Ethanol conversion at the 2 <sup>nd</sup> hour on stream at 550°C, 600°C, 650°C, 700°C and 750°C reaction temperature for various catalysts.....	137
<b>Figure 54(a):</b>	Ethanol conversion at the 2 <sup>nd</sup> hour on stream and average conversion of 8 hours at 550°C reaction temperature for various catalysts.....	138
<b>Figure 54(b):</b>	Ethanol conversion at the 2 <sup>nd</sup> hour on stream at 600°C and 650°C reaction temperature for various catalysts.....	139
<b>Figure 54(c):</b>	Ethanol conversion at the 2 <sup>nd</sup> hour on stream at 700°C and 750°C reaction temperature for various catalysts.....	140
<b>Figure 55:</b>	Co-relation of BET-SA and Ethanol Conversion at 550°C for various catalysts.....	140
<b>Figure 56:</b>	Trend of ethanol conversion at 550°C and peak temperature of reduction of Ni for various catalysts.....	141
<b>Figure 57(a):</b>	Trend of activity at 550°C is compared with a surface area of Ni determined by O <sub>2</sub> chemisorption.....	143
<b>Figure 57(b):</b>	Trend of activity at 600°C and 650°C is compared with a Surface area of Ni determined by O <sub>2</sub> chemisorption.....	143
<b>Figure 58:</b>	Plot of conversion of ethanol at 550°C versus median Ni(0) size of R&S catalysts determined by HRTEM.....	144

<b>Figure 59:</b>	Plot of ethanol conversion in ESR at 550°C versus median Ni(0) particle size determined by HRTEM.....	145
<b>Figure 60:</b>	Trend of ethanol conversion 2 <sup>nd</sup> hour on stream at 550°C versus XRD crystallite size of NiO of calcined catalysts.....	146
<b>Figure 61:</b>	Plot of the yield of Hydrogen at 550°C versus XRD crystallite size of NiO in calcined catalysts.....	147
<b>Figure 62:</b>	Trend of Yield of H <sub>2</sub> at various Temperatures for various catalysts.....	148
<b>Figure 63:</b>	Trend of Yield of CO at various Temperatures for various catalysts.....	149
<b>Figure 64:</b>	Trend of Yield of CO <sub>2</sub> at various Temperatures for various catalysts.....	150
<b>Figure 65:</b>	Trend of H <sub>2</sub> /CO molar ratio at various reaction temperature.....	153
<b>Figure 66:</b>	Trend of H <sub>2</sub> /CO <sub>2</sub> molar ratio at various reaction temperature.....	154
<b>Figure 67:</b>	Trend of H <sub>2</sub> /CH <sub>4</sub> molar ratio at various reaction temperature.....	154
<b>Figure 68:</b>	Trend of Yield of Ethylene at various Temperatures for various catalysts.....	158
<b>Figure 69:</b>	Trend of Strong acidity of catalysts and corresponding Yield of Ethylene at 550°C and 750°C.....	159
<b>Figure 70:</b>	Trend of the yield of CH <sub>4</sub> with reaction temperature.....	160
<b>Figure 71:</b>	Decay constants of different catalysts at 550°C and 750°C.....	161
<b>Figure 72:</b>	Trend of Coke content of catalyst after operation at 750°C For 8 hours.....	165
<b>Figure 73:</b>	Trend of coke content and Strong Acidity of various catalysts.....	167
<b>Figure 74:</b>	Trend of coke content of the catalysts operated at 750°C for 8 hours and decay constants for conversion of ethanol with time on stream.....	168
<b>Figure 75:</b>	Trend of strong acidity by NH <sub>3</sub> -TPD and decay constant at 750°C.....	169
<b>Figure 76:</b>	Trend of Acetaldehyde Yield at various temperatures for various catalysts.....	170

<b>Figure 77:</b>	Trend of Acetone Yield at various temperatures for various catalysts.....	171
<b>Figure 78:</b>	Trend of Ethanol Conversion at 650°C for various catalysts.....	172
<b>Figure 79:</b>	Decay Constants of Ethanol Conversion at 650°C and 700°C for various catalysts.....	173
<b>Figure 80:</b>	Decay Constants of Ethanol Conversion operated at 8 hours and 80 hours at 650°C.....	174
<b>Figure 81:</b>	Decay Constants of Ethanol Conversion operated at 8 hours and 80 hours at 700°C.....	175
<b>Figure 82:</b>	Coke deposits for various catalysts operated at 8 hours and 80 hours at 700°C.....	176
<b>Figure 83:</b>	Average conversion of ethanol for various catalysts operated for 80 hours on stream.....	178
<b>Figure 84:</b>	Average yield of H <sub>2</sub> for catalysts operated for 80 hours at 650°C and 700°C.....	179
<b>Figure 85:</b>	Average yield of CO for catalysts operated for 80 hours at 650°C and 700°C.....	180
<b>Figure 86:</b>	Average yield of CO <sub>2</sub> for catalysts operated for 80 hours at 650°C and 700°C.....	181
<b>Figure 87:</b>	Trend of the H <sub>2</sub> /CO molar ratio for catalysts operated for 80 hours at 650°C and 700°C.....	181
<b>Figure 88:</b>	Trend of the H <sub>2</sub> /CO <sub>2</sub> molar ratio for catalysts operated for 80 hours at 650°C and 700°C.....	182
<b>Figure 89:</b>	TEM of AMZ-0-89-0 a) Reduced catalyst and b) After use for ESR.....	183
<b>Figure 90:</b>	HRTEM of AMZ-44-44-0 a) Reduced catalyst and b) After use for ESR.....	184
<b>Figure 91:</b>	a) HRTEM details of 7.5% Ni-AMZ-29-59-0 and b) HRTEM details of 7.5%Ni-AMZ-44-44-0.....	185
<b>Figure 92:</b>	HRTEM of AMZ-39-49-0 a) Reduced catalyst and b) After use for ESR.....	186
<b>Figure 93:</b>	Magnified HRTEM image of 7.5%Ni-AMZ-39-49-0	

	showing Herringbone structure in carbon filament.....	187
<b>Figure 94:</b>	HRTEM of AMZ-29-59-0 a) Reduced catalyst and b) After use for ESR.....	187
<b>Figure 95:</b>	HRTEM of catalyst AMZ-44-0-44 a) Reduced catalyst and b) After use for ESR.....	188
<b>Figure 96:</b>	HRTEM of 7.5%Ni-AMZ-44-22-22 a) Reduced catalyst and b) After use for ESR.....	189
<b>Figure 97:</b>	HRTEM of 7.5%Ni-AMZ-22-44-22 a) Reduced catalyst and b) After use for ESR.....	190
<b>Figure 98:</b>	HR-TEM of 7.5%Ni-AMZ-22-22-44 a) Reduced catalyst and b) After use for ESR.....	190
<b>Figure 99:</b>	Trend of conversion of ethanol of the fresh catalyst and of the catalyst regenerated at 500°C.....	194
<b>Figure 100:</b>	Yield of H <sub>2</sub> of the fresh catalyst and of the regenerated catalyst.....	195
<b>Figure 101:</b>	Ethanol Conversion of Fresh and Regenerated catalyst calcined at 650°C.....	196
<b>Figure 102:</b>	Ethanol Conversion at Different Temperature for EDR Reaction for various catalysts.....	214
<b>Figure 103:</b>	Ethanol conversion at 550°C 2 <sup>nd</sup> hour and 550°C 8 hours average.....	215
<b>Figure 104:</b>	Ethanol conversion at 600°C and 650°C for various catalysts.....	216
<b>Figure 105:</b>	CO <sub>2</sub> conversion at various temperatures for EDR Reaction.....	217
<b>Figure 106:</b>	CO <sub>2</sub> conversion at 550°C temperature for various catalyst.....	218
<b>Figure 107:</b>	Yield of H <sub>2</sub> (mol%) at various temperature for various catalyst.....	219
<b>Figure 108:</b>	Yield of CO (mol%) at various temperature for various catalyst.....	221
<b>Figure 109:</b>	Trend of ratio of Ethanol Conversion/CO <sub>2</sub> conversion at various temperature for various catalysts.....	223
<b>Figure 110:</b>	Trend of H <sub>2</sub> /CO molar ratio at various temperatures for various catalysts.....	224

<b>Figure 111:</b>	Trend of H <sub>2</sub> /CH <sub>4</sub> molar ratio at various temperatures for various catalysts.....	225
<b>Figure 112:</b>	Trend of Yield of Ethylene at various temperatures for various catalysts.....	228
<b>Figure 113:</b>	Trend of Yield of Ethylene at 550°C and 750°C with Strong acidity of various catalysts.....	229
<b>Figure 114:</b>	Trend of Yield of Methane at various temperatures for various catalysts.....	230
<b>Figure 115:</b>	Coke formation of various catalysts operated at 750°C for 8 hours.....	231
<b>Figure 116:</b>	Comparison of coke content of spent catalysts used for short duration (8 hours) ESR and EDR runs.....	232
<b>Figure 117:</b>	Trend of Coke content and Strong acidity for various catalyst.....	233
<b>Figure 118:</b>	Trend of decay constants at 550°C and 750°C for 8 hours runs at various temperature for various catalysts.....	234
<b>Figure 119:</b>	Trend of relation between the magnitude of the decay constant and the coke content of spent catalysts operated at 750°C for 8 hours.....	236
<b>Figure 120:</b>	Ethanol Conversion for 7.5%Ni-AMZ-44-0-44 Catalyst at 650°C and 700°C.....	237
<b>Figure 121:</b>	CO <sub>2</sub> Conversion for 7.5%Ni-AMZ-44-0-44 Catalyst at 650°C and 700°C.....	238
<b>Figure 122:</b>	Ethanol Conversion for 7.5%Ni-AMZ-22-44-22 Catalyst at 650°C and 700°C.....	239
<b>Figure 123:</b>	CO <sub>2</sub> Conversion for 7.5%Ni-AMZ-22-44-22 Catalyst at 650°C and 700°C.....	239
<b>Figure 124:</b>	HRTEM micrograph of catalyst 7.5%Ni-AMZ-44-0-44.....	240
<b>Figure 125:</b>	HRTEM of the spent catalyst 7.5%Ni-AMZ-22-44-22.....	241
<b>Figure 126:</b>	Ethanol conversion for the fresh and regenerated 7.5%Ni-AMZ-22-44-22 catalyst.....	242